

Schmierstoffe Deutschland

RZ10R Radiator Flush

RZ10R Radiator Flush is formulated with additives that circulate through the cooling system to remove scale, loosen rust, mineral deposits and oily residues.


- Cleans all from engine-block to radiator and heater cores.
- Clears blockages which can cause overheating. Restores effective cooling and improves heater performance.
- Restores the function of valves, thermostats and water pumps.
- Excellent performance in all types of cooling liquid, including OAT coolant.
- Suitable for all radiator types, and harmless to rubber hoses and gasket materials.

Application:

Gasoline and diesel engine cooling system.

Usage direction:

One bottle (250ml) treats for at most 12L coolant. Add directly into radiator before changing coolant. Run engine and idle for 15 minutes, drain, or wash with professional equipment.



Content: 250 ml

Content Carton: 12 Bottles

Typical characteristics

Typical characteristics			
Property	Method	Unit	Value
Colour		-	colorless
Odor		-	Characteristic odour
Physical state		-	fluid
Kinematic viscosity	ISO 3104/ <mark>3105</mark>	g/ml	1,2
Boiling point and boiling range		°C	100
Flash point	DIN EN ISO 2592	°C	>93
Autoflammability		°C	>200
Relative density		g/ml	1,01
Water solubility		-	Miscible in all proportions

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.



