



RZ400 5W40 Engine Oil

RZ400 5W40 is a high-quality engine oil based on HC synthesis and was developed to meet the needs of modern petrol and diesel vehicles. It is suitable for vehicles with gasoline and diesel engines, with and without turbocharging, and is used for vehicles without extended maintenance intervals. It enables a wide range of uses and under all operating conditions.

Compatibility:

- ACEA A3/B4
- API SN/CF
- MB 229.3
- PSA B71 2296
- Renault RN 0700/0710
- VW 502 00/505 00

Advantages:

- suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking
- Safer year-round operation
- Good cold-starting properties and rapid engine lubrication
- Stable lubricating film, even with hot oil and under excessive loads
- Low oil consumption
- High level of oxidation protection
- Proper functioning of hydraulic tappets

Our synthetic motor oil RZ400 provides excellent protection against wear and oxidation in cars, light and heavy trucks. It also offers unmatched temperature stability to get the best performance for the engine in harsh conditions.

Content: 4,0 Liter

Content Carton: 4 cans

Content: 60,0 Liter

Content Sea pallet: 9 drums

Content: 200,0 Liter

Content Sea pallet: 4 drums



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,849
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	85,7
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,4
Viscosity index	ASTM D-7042	-	175
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	240
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-36
CCS	ASTM D-5293	cP @ °C	5800 @ -30
Total base number	DIN 51639-1	mgKOH/g	10,6
HTHS	ASTM D4683	mPas	4,2
Sulphated ash	ASTM D874	weight-%	≤ 1,6

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.