

Schmierstoffe Deutschland

RZ800 5W30 Engine Oil


RZ800 5W30 high-performance fully synthetic motor oil is formulated for ultimate engine performance and protection under all operating conditions. It provides better fuel economy, reduces emission and prolongs engine lives with excellent wear protection and friction reduction. It is used in gasoline, LPG and diesel engines of passenger cars and light-duty commercial vehicles equipped with soot filters.

Compatibility:

- API SN / CF
- ACEA C3
- BMW Longlife-04
- MB 229.52 / 229.51 / 229.31
- VW 502 00/505 00/505 01
- Dexos 2

Advantages:

- First-class economy grade for multi-functional use in diesel and Otto engines from different manufacturers
- The low sulphated ash, low phosphorus and Sulphur content protects diesel particulate filters and catalytic converters
- Hinders the formation of deposits in the engine. As a result, it guarantees first-rate operational safety performance and low maintenance costs
- Low oil consumption due to a very low evaporation loss
- Good cold-starting properties and rapid engine lubrication



Content: 1,0 Liter Content: 4,0 Liter Content Carton: 10 cans Content Carton: 4 cans Content: 60,0 Liter Content: 200.0 Liter Content Sea pallet: 9 drums Content Sea pallet: 4 drums

Typical characteristics

Typical characteristics					
Property		Method		Unit	Value
Density at 15 °C		ASTM D-7042		g/ml	0,85
Kinematic viscosity KV 40		ASTM D-7 <mark>042</mark>		mm²/s	69
Kinematic viscosity KV 100		ASTM D-7 <mark>042</mark>		mm²/s	12
Viscosity index		ASTM D-7042		-	170
Flash point		ASTM D-92 / DIN EN ISO 2	2592	°C	240
Pour point		ASTM D-97 / DIN EN ISO 3016		°C	-36
CCS		ASTM D-5293		cP @ °C	5400 @ -30
Total base number		DIN 51639-1		mgKOH/g	7,2
HTHS		ASTM D4683		mPas	3,51

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

